

# iCan Screen 13,3"

## 13,3" full HD Display - TFT Color LCD

iCan Screen 13.3" is a multi-purpose ruggedized display specially designed for avionics applications.



### Main Features

- Customizable HMI software can be developed according to your specifications and then downloaded into the display.
- User can select the video source and display up to 4 different sources on one screen.
- Several displays can be chained without any additional device (e.g. one external IP camera displayed on all screens), and one storage media can be shared by multiple displays.
- External camera can be powered using 12 VDC output or Ethernet POE.
- Tactile buttons with force feedback and a luminosity sensor enable to control the brightness of the screen manually or automatically and to secure operations during the flight
- iCan Screen 6,5" is also DO254/DO178-C

### Interfaces

1 x HD-SDI 75 Ohm video input  
1 x NTSC Differential 100 Ohm video input  
2 x Ethernet 1000 Mbit/s POE 802.3 af  
1 x NTSC Differential 100 Ohm video output  
Reading media contents: 1 x USB and 1 x internal SD Card  
Rear connector : DMM Micro-connector 47 pins  
Luminosity sensor  
Tactile buttons : - Luminosity + / -  
- One programmable button

### Physical specifications

**Size (LxWxH mm):** 353 x 200 x 37.7  
**Weight (kg):** 2,35 (+/- 100g)

### Typical application

- This equipment can be installed in the cockpit cabin areas
- It is designed to be easily integrated into
  - In-Flight Entertainment,
  - Cabin Management Systems for Cockpit Door Surveillance System (CDSS),
  - full cabin control,
  - displaying multimedia and camera contents.

### Display

<b>Diagonal size:</b>	13,3" (33,78cm)
<b>Resolution:</b>	1920 x 1080 pixels (FHD)
<b>Technology:</b>	TFT Color LCD
<b>Colors:</b>	16 Millions
<b>Luminosity:</b>	400 Cd/m <sup>2</sup>
<b>Contrast ratio:</b>	700:1 (500:1mini)
<b>Viewing angle:</b>	140° or 170°

### Miscellaneous

<b>Power supply:</b>	17 VDC to 32 VDC
<b>Power consumption:</b>	26 W max
<b>Temp. Range:</b>	-15°C / +55°C (functional)
<b>Processor:</b>	Apalis iMX6 - 2 GB
<b>Operating System:</b>	Linux Angstrom
<b>Qualification:</b>	RTCA DO-160G
<b>Certifiable:</b>	DO254, DO178-C (DAL D)
<b>Touch display:</b>	Option

### More Information

[info@oxytronic.fr](mailto:info@oxytronic.fr)

[www.oxytronic.fr](http://www.oxytronic.fr)

